

- Easy programming using selection button sequence
- Electronic control and data-recording
- Energy management by real time clock
- Electronically controlled forced air-cooling
- Each column has individual vend motor
- 24 V D/C motors
- Interchangeable parts



### Model

### VDI 544-8

|                          |        |
|--------------------------|--------|
| Selections / Columns     | 10 / 8 |
| Max. product length (mm) | 505    |
| Max. product Ø (mm)      | 72     |

#### Capacities:

|            |        |     |
|------------|--------|-----|
| Can        | 0,33 l | 544 |
| PET bottle | 0,50 l | 272 |

#### Dimensions and weights:

|                |                  |
|----------------|------------------|
| H x W x D (mm) | 1830 x 850 x 940 |
| Weight         | 335 kg           |

#### Performance data:

|                        |               |
|------------------------|---------------|
| Refrigeration          | 0,997 kW      |
| Power supply           | 230 V / 50 Hz |
| Max. power consumption | 875 W         |

|         |                                      |
|---------|--------------------------------------|
| Control | Executive; MDB                       |
| Cabinet | Zinc coated steel,<br>powder painted |

#### Standard:

- Black cabinet
- 5 digit display
- Safety coin return
- Anti-vandalism panel in selection button area
- Cut out or validator or alternative payment system
- Lock
- Choice of neutral front poster

#### Options:

- Cabinet colour on request
- Two-line LCD display
- Security cash system
- Safety sliding coin insert
- Anti-rain kit IP 34
- Loading rack
- DEX / UCS interface
- Special coded lock
- Individual graphics

