



## AA UC800C Under Sink Chiller with Chrome Faucet A Compact, Discreet and Stylish drinking water solution



<b>Model</b>	UC800C
<b>Cold Water</b>	1.3GAL of 50°F/HR(5L of 10°C)
	Based ARI Standard from water inlet temperature of 26.7 C and ambient temperature of 32.2 C
<b>Room Temp. Water</b>	N/A
<b>Dimensions</b>	16.1"W(410mm)X8.3"D(210mm)X14.4"H(290mm)
<b>Weight</b>	27.6lbs(12.5kg)
<b>Shipping Dimensions</b>	18.3"W(465mm)X9.0"D(230mm)X13.0"H(330mm)
<b>Shipping Weight</b>	30.9lbs(14kg)
<b>Inlet/Outlet Pipe Diameter</b>	1/4"(External Diameter)X0.170"(Internal Diameter)
<b>Optimum Material</b>	LLDPE (Line Low Density Poly Ethylene)
<b>Faucet as standard</b>	Attractive chrome faucet with 1/4" pipe attached
<b>Allowed Pressure</b>	700kPa
<b>Cabinet</b>	High quality material with strong corrosion resistance.
<b>Cold Water Tank</b>	Hygienic stainless steel. External refrigerant evaporator which is mechanically wrapped around tank.
<b>Cold Water Thermostat</b>	Temperature is controlled to 35.6°F~53.6°F(2°C~12°C) by adjustable thermostat, easily accessible at the back of cabinet.
<b>Refrigeration unit</b>	Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. Refrigerant is controlled by accurately calibrated capillary tube. Highly efficient cooling system.
<b>Refrigerant type</b>	R134a
<b>Electrical</b>	220V ~ 240V (±10%) 50/60Hz, 100V ~ 127V (±10%) 50/60Hz provided with power cord.
<b>Quality</b>	Our models covered by these specifications are manufactured to comply with the standards of overseas quality system. CE approved
<b>Warranty</b>	One year on the sealed refrigeration system and most component parts.

**AA First a Division of Circon Limited Registered in England 5121722**

Cedar House, Grange Farm, Long Lane, Newbury, RG14 2TF

Tel: +44(0)1635 202489 Fax: +44(0)1635 202499

Email: enquiry@aafirst.co.uk.