Kikko Max





Kikko Max is the free standing vending machine with a 620 cup capacity and up to 7 canisters which complements the Necta Hot & Cold range. With a height of 1830 mm, it has been designed to stand alongside the similarly sized Snakky Max or Sfera machines. The Kikko Max works in a master/salve mode and utilizes a single payment system which provides "One-Stop-Shopping" and creates an appealing machine bank, ensuring the most user friendly and practical vending service available.

ELECTRONIC CONTROL

The 16-bit electronic control with incorporated flash EPROM is extremely flexible and complete, as well as being compatible with the PC application GIGA. This allows a palmtop to be connected, via an RS232 interface, to allow the automatic set-up of the machine as well as the downloading of sales statistics and data (also in EVA-DTS format). With GIGA it is also possible to have remote monitoring of the machine using GSM technology.

PAYMENT SYSTEMS

Kikko Max is pre-set for the installation of systems with Executive, BDV and MDB protocol as well as for installation of validators.

At the same time, the following can be fitted:

- Change-giver, validator or coin mechanism
- Bill acceptor
- · Cashless system with key or card.

ACCESSORIES

Mechanical selections counter kit Lid for coin box kit Cup sensor + cup station lamp kit Cup station lamp kit 20 litre water tank kit 2x20 litre water tanks kit Still cooling unit kit (for powders) Master/slave kit RS232 jack kit GSM kit



POWER CONSUMPTION

Espresso version To reach operating temperature For each hour of stand-by	51.71 Wh 100 Wh
Instant version To reach operating temperature For each bour of stand-by	174.1 Wh 88 7 Wh

CAPACITY		
Cups (Ø 70-71 mm)	620*	
Stirrers (length 95/105 mm)	550	
Containers	6 ES / 7 IN	
Espresso boiler	0.6 I	
Instant boiler	2	
Coffee beans	3.2 kg	
Instant coffee	0.9 kg ES / 1.2 kg IN	
Chocolate	5.2 kg	
Milk	2.6 kg	
Tea	3.2 kg	
Sugar	4 kg	
*166 cc	,	

CHARACTERISTICS		
Height	1830 mm*	
Width	540 mm	
Depth	650 mm	
Overall depth with door open	1120 mm	
Weight	126 kg ca.	
Power supply voltage	230 V	
Power supply frequency	50 Hz	
Installed power	1800 W	
Water mains pressure (With 3/4" gas male connection)	0.5 to 8.5 bar	
*Adjustable feet: +10 -10 mm		



EXAMPLES OF POSSIBLE CONFIGURATIONS

	KIKKO MAX ES 6 (Espresso Unit + 5 canisters)	KIKKO MAX IN 7 (7 canisters)
Pre-selections		
Sugar dosing	<u>=</u>	.
Bean coffee black	■ ;	
Bean coffee long	<u></u>	
Bean café au lait	î)	
Bean coffee white	Î	
Instant espresso coffee		<u></u>
Coffee long		<u>=</u>
Café au lait		<u>=</u>
Coffee white		_
Cappuccino	<u>=</u>	<u></u>
Chocolate	<u> </u>	<u>=</u>
Chocolate strong	<u> </u>	<u>=</u>
Chocomilk	<u> </u>	<u>=</u>
Decaf/Instant coffee black	Î)	<u> </u>
Decaf/Instant coffee long	Î	<u></u>
Decaf/Instant café au lait	Î	<u> </u>
Decaf/Instant cappuccino		<u>=</u> :
Lemon tea	<u> </u>	<u>=</u>
Soup		<u> </u>
Milk/Hot water	<u> </u>	<u></u>
Cup only	Î	<u></u>
No cup	<u>=</u>	



EVOCA SPA

Via Roma 24 - 24030 Valbrembo (BG) Italia Tel +39 035 606111 - fax +39 035 606519